## Microsoft® LifeCam Show™



## World-Class HD Optics | Always Focused

Version Information	
Product Version	Microsoft® LifeCam Show™
Webcam Version	Microsoft LifeCam Show v1.0
Product Dimensions	microsoft Endeath Choir 1110
Webcam Length	2.44 inches (62 millimeters)
Webcam Width	1.26 inches (32 millimeters)
Webcam Depth/Height	0.48 inches (12.3 millimeters)
Webcam Weight	1.51 ounces (42.8 grams)
Webcam Cable Length	72.0 inches (1829 millimeters)
Compatibility and Localization	
Interface	High-speed USB compatible with the USB 2.0 specification
Operating Systems	Microsoft Windows® Vista® and Windows XP with Service Pack 2 (SP2)
Top-line System Requirements	Requires a PC that meets the requirements for and has installed one of these operating systems:
	Microsoft Windows Vista
	Intel Pentium® 4 2.8 GHz (Pentium Dual Core 2.0 GHz recommended)
	• 1 GB of RAM (2 GB recommended)
	• 200-600 MB hard drive space
	• Windows XP with Service Pack 2 (SP2)
	Intel Pentium® 4 1.8 GHz (Pentium Dual Core 1.8 GHz recommended)     256 MB of RAM (500 MB recommended)
	• 400-1250 MB hard drive space
	Display adapter capable of 16-bit color depth or higher
	• 2 MB or higher video memory
	Windows-compatible speakers or headphones
	• USB 1.1 (USB 2.0 recommended). USB port 2.0 required for 1.3 MP and above video capture resolution. System without USB 2.0 may
	achieve 800 x 600 pixel resolution
	• CD-ROM drive
	Broadband internet access required; access fees may apply
	Microsoft LifeCam software, version 1.4
	Internet functions (post to Windows Live™ Spaces, send in e-mail, video calls), also require: Internet Explorer® 6/7 browser software
	required for installation; 25 MB hard drive space typically required (users can maintain other default Web browsers after installation)
0	
Compatibility Logos	Certified for Microsoft Windows Vista     Certified High-Speed USB logo
Software Localization	Microsoft Lifecam software version 1.4 may be installed in Simplified Chinese, Traditional Chinese, English, French, German, Italian,
Software Localization	Japanese, Korean, Brazilian Portuguese, Iberian Portuguese, or Spanish. If available, standard setup will install the software in the default
	Josephiness, fiverent, prazimant in uniquess, iberiant in uniquesse, or parametri. In available, stational setup will install the software in the detault OS language. Otherwise, the English language version will be installed.
Windows Live <sup>™</sup> Integration Features	Of language. Otherwise, the English language version will be installed.
Video Conversation Feature	Windows Live Call button delivers one touch access to video conversation. Photo Swap allows you to share and swap photos during a live
video Conversation i eature	video call.
Call Button Life	
Call Button Life Webcam Controls & Effects	4,000 actuations
Webcam Controls & Effects	4,000 actuations  LifeCam Dashboard provides access to animated video special effect features and webcam controls
Webcam Controls & Effects Blogging Feature	4,000 actuations
Webcam Controls & Effects	4,000 actuations  LifeCam Dashboard provides access to animated video special effect features and webcam controls
Webcam Controls & Effects Blogging Feature Imaging Features	4,000 actuations  LifeCam Dashboard provides access to animated video special effect features and webcam controls  Add photos to Windows Live Spaces with one mouse click
Webcam Controls & Effects Blogging Feature Imaging Features Sensor	4,000 actuations  LifeCam Dashboard provides access to animated video special effect features and webcam controls  Add photos to Windows Live Spaces with one mouse click  CMOS 2.0 sensor technology
Webcam Controls & Effects Blogging Feature Imaging Features Sensor	4,000 actuations  LifeCam Dashboard provides access to animated video special effect features and webcam controls  Add photos to Windows Live Spaces with one mouse click  CMOS 2.0 sensor technology  • Motion Video: 800X600 pixel resolution*
Webcam Controls & Effects Blogging Feature Imaging Features Sensor Resolution	4,000 actuations  LifeCam Dashboard provides access to animated video special effect features and webcam controls  Add photos to Windows Live Spaces with one mouse click  CMOS 2.0 sensor technology  • Motion Video: 800X600 pixel resolution*  • Still Image: 8.0 megapixel interpolated*
Webcam Controls & Effects Blogging Feature Imaging Features Sensor Resolution Field of View	4,000 actuations  LifeCam Dashboard provides access to animated video special effect features and webcam controls  Add photos to Windows Live Spaces with one mouse click  CMOS 2.0 sensor technology  • Motion Video: 800X600 pixel resolution*  • Still Image: 8.0 megapixel interpolated*  67° diagonal field of view  • Digital pan, digital tilt, vertical tilt, and swivel pan, and 5x digital zoom  • Always focused from 21" to 60" depth of field
Webcam Controls & Effects Blogging Feature Imaging Features Sensor Resolution Field of View Imaging Features	4,000 actuations  LifeCam Dashboard provides access to animated video special effect features and webcam controls  Add photos to Windows Live Spaces with one mouse click  CMOS 2.0 sensor technology  • Motion Video: 800X600 pixel resolution*  Still Image: 8.0 megapixel interpolated*  67° diagonal field of view  • Digital pan, digital tilt, vertical tilt, and swivel pan, and 5x digital zoom
Webcam Controls & Effects Blogging Feature Imaging Features Sensor Resolution Field of View Imaging Features Product Feature Performance	4,000 actuations  LifeCam Dashboard provides access to animated video special effect features and webcam controls  Add photos to Windows Live Spaces with one mouse click  CMOS 2.0 sensor technology  • Motion Video: 800X600 pixel resolution*  • Still Image: 8.0 megapixel interpolated*  67° diagonal field of view  • Digital pan, digital tilt, vertical tilt, and swivel pan, and 5x digital zoom  • Always focused from 21" to 60" depth of field  • Automatic image adjustment with manual overwrite
Webcam Controls & Effects Blogging Feature Imaging Features Sensor Resolution Field of View Imaging Features  Product Feature Performance Audio Features	4,000 actuations  LifeCam Dashboard provides access to animated video special effect features and webcam controls  Add photos to Windows Live Spaces with one mouse click  CMOS 2.0 sensor technology  • Motion Video: 800X600 pixel resolution*  Still Image: 8.0 megapixel interpolated*  67° diagonal field of view  • Digital pan, digital tilt, vertical tilt, and swivel pan, and 5x digital zoom  • Always focused from 21" to 60" depth of field  • Automatic image adjustment with manual overwrite  Integrated microphone and noise cancellation
Webcam Controls & Effects Blogging Feature Imaging Features Sensor Resolution Field of View Imaging Features  Product Feature Performance Audio Features Microphone technology	4,000 actuations  LifeCam Dashboard provides access to animated video special effect features and webcam controls  Add photos to Windows Live Spaces with one mouse click  CMOS 2.0 sensor technology  • Motion Video: 800X600 pixel resolution*  • Still Image: 8.0 megapixel interpolated*  67° diagonal field of view  • Digital pan, digital tit, vertical tilt, and swivel pan, and 5x digital zoom  • Always focused from 21" to 60" depth of field  • Automatic image adjustment with manual overwrite  Integrated microphone and noise cancellation  Unidirectional noise cancelling microphone
Webcam Controls & Effects Blogging Feature Imaging Features Sensor Resolution Field of View Imaging Features  Product Feature Performance Audio Features	4,000 actuations  LifeCam Dashboard provides access to animated video special effect features and webcam controls  Add photos to Windows Live Spaces with one mouse click  CMOS 2.0 sensor technology  • Motion Video: 800X600 pixel resolution*  • Still Image: 8.0 megapixel interpolated*  67° diagonal field of view  • Digital pan, digital tilt, vertical tilt, and swivel pan, and 5x digital zoom  • Always focused from 21" to 60" depth of field  • Automatic image adjustment with manual overwrite  Integrated microphone and noise cancellation  Unidirectional noise cancelling microphone  • Webcam Stand (2.8 X 2.6 X 11.4 inches)
Webcam Controls & Effects Blogging Feature Imaging Features Sensor Resolution Field of View Imaging Features  Product Feature Performance Audio Features Microphone technology Mounting Features	4,000 actuations  LifeCam Dashboard provides access to animated video special effect features and webcam controls  Add photos to Windows Live Spaces with one mouse click  CMOS 2.0 sensor technology  • Motion Video: 800X600 pixel resolution*  • Still Image: 8.0 megapixel interpolated*  67° diagonal field of view  • Digital pan, digital tilt, vertical tilt, and swivel pan, and 5x digital zoom  • Always focused from 21" to 60" depth of field  • Automatic image adjustment with manual overwrite  Integrated microphone and noise cancellation  Unidirectional noise cancelling microphone  • Webcam Stand (2.8 X 2.6 X 11.4 inches)  • Universal Mounting Clip
Webcam Controls & Effects Blogging Feature Imaging Features Sensor Resolution Field of View Imaging Features  Product Feature Performance Audio Features Microphone technology Mounting Features  Additional Features	4,000 actuations  LifeCam Dashboard provides access to animated video special effect features and webcam controls  Add photos to Windows Live Spaces with one mouse click  CMOS 2.0 sensor technology  • Motion Video: 800X600 pixel resolution*  Still Image: 8.0 megapixel interpolated*  67° diagonal field of view  • Digital pan, digital tilt, vertical tilt, and swivel pan, and 5x digital zoom  • Always focused from 21" to 60" depth of field  • Automatic image adjustment with manual overwrite  Integrated microphone and noise cancellation  Unidirectional noise cancelling microphone  • Webcam Stand (2.8 X 2.6 X 1.1.4 inches)  • Universal Mounting Clip  Carrying Case Included
Webcam Controls & Effects Blogging Feature Imaging Features Sensor Resolution Field of View Imaging Features  Product Feature Performance Audio Features Microphone technology Mounting Features  Additional Features Storage Temperature & Humidity	4,000 actuations  LifeCam Dashboard provides access to animated video special effect features and webcam controls  Add photos to Windows Live Spaces with one mouse click  CMOS 2.0 sensor technology  • Motion Video: 800X600 pixel resolution*  • Still Image: 8.0 megapixel interpolated*  67° diagonal field of view  • Digital pan, digital tilt, vertical tilt, and swivel pan, and 5x digital zoom  • Always focused from 21" to 60" depth of field  • Automatic image adjustment with manual overwrite  Integrated microphone and noise cancellation  Unidirectional noise cancelling microphone  • Webcam Stand (2.8 X 2.6 X 11.4 inches)  • Universal Mounting Clip  Carrying Case Included  -40 °F (-40 °C) to 140 °F (60 °C) at <5% to 65% relative humidity (non-condensing)
Webcam Controls & Effects Blogging Feature Imaging Features Sensor Resolution Field of View Imaging Features  Product Feature Performance Audio Features Microphone technology Mounting Features  Additional Features Storage Temperature & Humidity Operating Temperature & Humidity	4,000 actuations  LifeCam Dashboard provides access to animated video special effect features and webcam controls  Add photos to Windows Live Spaces with one mouse click  CMOS 2.0 sensor technology  • Motion Video: 800X600 pixel resolution*  Still Image: 8.0 megapixel interpolated*  67° diagonal field of view  • Digital pan, digital tilt, vertical tilt, and swivel pan, and 5x digital zoom  • Always focused from 21" to 60" depth of field  • Automatic image adjustment with manual overwrite  Integrated microphone and noise cancellation  Unidirectional noise cancelling microphone  • Webcam Stand (2.8 X 2.6 X 1.1.4 inches)  • Universal Mounting Clip  Carrying Case Included
Webcam Controls & Effects Blogging Feature Imaging Features Sensor Resolution Field of View Imaging Features  Product Feature Performance Audio Features Microphone technology Mounting Features  Additional Features Storage Temperature & Humidity Operating Temperature & Humidity Certification Information	4,000 actuations  LifeCam Dashboard provides access to animated video special effect features and webcam controls  Add photos to Windows Live Spaces with one mouse click  CMOS 2.0 sensor technology  • Motion Video: 800X600 pixel resolution*  • Still Image: 8.0 megapixel interpolated*  67° diagonal field of view  • Digital pan, digital tilt, vertical tilt, and swivel pan, and 5x digital zoom  • Always focused from 21" to 60" depth of field  • Automatic image adjustment with manual overwrite  Integrated microphone and noise cancellation  Unidirectional noise cancelling microphone  • Webcam Stand (2.8 X 2.6 X 11.4 inches)  • Universal Mounting Clip  Carrying Case Included  -40 "F (-40 "C) to 140 °F (60 °C) at <5% to 65% relative humidity (non-condensing)  32° F (0° C) to 104 °F (40 °C) at <5% to 80% relative humidity (non-condensing)
Webcam Controls & Effects Blogging Features Imaging Features Sensor Resolution Field of View Imaging Features  Product Feature Performance Audio Features Microphone technology Mounting Features  Additional Features Storage Temperature & Humidity Operating Temperature & Humidity Certification Information Model No.	4,000 actuations  LifeCam Dashboard provides access to animated video special effect features and webcam controls  Add photos to Windows Live Spaces with one mouse click  CMOS 2.0 sensor technology  • Motion Video: 800X600 pixel resolution*  • Still Image: 8.0 megapixel interpolated*  67° diagonal field of view  • Digital pan, digital tilt, vertical tilt, and swivel pan, and 5x digital zoom  • Always focused from 21" to 60" depth of field  • Automatic image adjustment with manual overwrite  Integrated microphone and noise cancellation  Unidirectional noise cancelling microphone  • Webcam Stand (2.8 X 2.6 X 1.1.4 inches)  • Universal Mounting Clip  Carrying Case included  -40 °F (-40 °C) to 140 °F (60 °C) at <5% to 65% relative humidity (non-condensing)  132° F (0° C) to 104 °F (40 °C) at <5% to 80% relative humidity (non-condensing)
Webcam Controls & Effects Blogging Feature Imaging Features Sensor Resolution Field of View Imaging Features  Product Feature Performance Audio Features Microphone technology Mounting Features  Additional Features Storage Temperature & Humidity Operating Temperature & Humidity Certification Information Model No. Country of Manufacture	4,000 actuations  LifeCam Dashboard provides access to animated video special effect features and webcam controls  Add photos to Windows Live Spaces with one mouse click  CMOS 2.0 sensor technology  • Motion Video: 800X600 pixel resolution*  • Still Image: 8.0 megapixel interpolated*  67° diagonal field of view  • Digital pan, digital tilt, vertical tilt, and swivel pan, and 5x digital zoom  • Always focused from 21" to 60" depth of field  • Automatic image adjustment with manual overwrite  Integrated microphone and noise cancellation  Unidirectional noise cancelling microphone  • Webcam Stand (2.8 X 2.6 X 11.4 inches)  • Universal Mounting Clip  Carrying Case Included  -40 "F (-40 "C) to 140 °F (60 °C) at <5% to 65% relative humidity (non-condensing)  32° F (0° C) to 104 °F (40 °C) at <5% to 80% relative humidity (non-condensing)
Webcam Controls & Effects Blogging Features Imaging Features Sensor Resolution Field of View Imaging Features  Product Feature Performance Audio Features Microphone technology Mounting Features  Additional Features Storage Temperature & Humidity Operating Temperature & Humidity Certification Information Model No.	4,000 actuations  LifeCam Dashboard provides access to animated video special effect features and webcam controls  Add photos to Windows Live Spaces with one mouse click  CMOS 2.0 sensor technology  • Motion Video: 800X600 pixel resolution*  • Still Image: 8.0 megapixel interpolated*  67° diagonal field of view  • Digital pan, digital titt, vertical tilt, and swivel pan, and 5x digital zoom  • Always focused from 21" to 60" depth of field  • Automatic image adjustment with manual overwrite  Integrated microphone and noise cancellation  Unidirectional noise cancelling microphone  • Webcam Stand (2.8 X 2.6 X 11.4 inches)  • Universal Mounting Clip  Carrying Case Included  4-40 °F (-40 °C) to 140 °F (60 °C) at <5% to 65% relative humidity (non-condensing)  1355  People's Republic of China (PRC)  Yes
Webcam Controls & Effects Blogging Feature Imaging Features Sensor Resolution Field of View Imaging Features  Product Feature Performance Audio Features  Microphone technology Mounting Features  Additional Features  Storage Temperature & Humidity Operating Temperature & Humidity Certification Information Model No. Country of Manufacture ISO 9001 Qualified Manufacturer	4,000 actuations  LifeCam Dashboard provides access to animated video special effect features and webcam controls  Add photos to Windows Live Spaces with one mouse click  CMOS 2.0 sensor technology  • Motion Video: 800X600 pixel resolution*  • Still Image: 8.0 megapixel interpolated*  67° diagonal field of view  • Digital pan, digital tilt, vertical tilt, and swivel pan, and 5x digital zoom  • Always focused from 21" to 60" depth of field  • Automatic image adjustment with manual overwrite  Integrated microphone and noise cancellation  Unidirectional noise cancelling microphone  • Webcam Stand (2.8 X 2.6 X 11.4 inches)  • Universal Mounting Clip  Carrying Case Included  -40 °F (-40 °C) to 140 °F (60 °C) at <5% to 65% relative humidity (non-condensing)  32° F (0° C) to 104 °F (40 °C) at <5% to 80% relative humidity (non-condensing)
Webcam Controls & Effects Blogging Feature Imaging Features Sensor Resolution Field of View Imaging Features  Product Feature Performance Audio Features  Microphone technology Mounting Features  Additional Features  Storage Temperature & Humidity Operating Temperature & Humidity Certification Information Model No. Country of Manufacture ISO 9001 Qualified Manufacturer	4,000 actuations  LifeCam Dashboard provides access to animated video special effect features and webcam controls  Add photos to Windows Live Spaces with one mouse click  CMOS 2.0 sensor technology  • Motion Video: 800X600 pixel resolution*  • Still Image: 8.0 megapixel interpolated*  67° diagonal field of view  • Digital pan, digital tilt, vertical tilt, and swivel pan, and 5x digital zoom  • Always focused from 21" to 60" depth of field  • Automatic image adjustment with manual overwrite  Integrated microphone and noise cancellation  Unidirectional noise cancelling microphone  • Webcam Stand (2.8 X 2.6 X 11.4 inches)  • Universal Mounting Clip  Carrying Case Included  -40 °F (-40 °C) to 140 °F (60 °C) at <5% to 65% relative humidity (non-condensing)  32° F (0° C) to 104 °F (40 °C) at <5% to 80% relative humidity (non-condensing)  1355  People's Republic of China (PRC)  Yes  • FCC Declaration of Conformity (USA)
Webcam Controls & Effects Blogging Feature Imaging Features Sensor Resolution Field of View Imaging Features  Product Feature Performance Audio Features  Microphone technology Mounting Features  Additional Features  Storage Temperature & Humidity Operating Temperature & Humidity Certification Information Model No. Country of Manufacture ISO 9001 Qualified Manufacturer	4,000 actuations  LifeCam Dashboard provides access to animated video special effect features and webcam controls  Add photos to Windows Live Spaces with one mouse click  CMOS 2.0 sensor technology  • Motion Video: 800X600 pixel resolution*  Still Image: 8.0 megapixel interpolated*  67° diagonal field of view  • Digital pan, digital tilt, vertical tilt, and swivel pan, and 5x digital zoom  • Always focused from 21" to 60" depth of field  • Automatic image adjustment with manual overwrite  Integrated microphone and noise cancellation  Unidirectional noise cancelling microphone  • Webcam Stand (2.8 X 2.6 X 11.4 inches)  • Universal Mounting Clip  Carrying Case Included  -40 °F (-40 °C) to 140 °F (60 °C) at <5% to 65% relative humidity (non-condensing)  1355  People's Republic of China (PRC)  Yes  • FCC Declaration of Conformity (USA)  • UL and cUL Listed Accessory (USA and Canada)
Webcam Controls & Effects Blogging Feature Imaging Features Sensor Resolution Field of View Imaging Features  Product Feature Performance Audio Features  Microphone technology Mounting Features  Additional Features  Storage Temperature & Humidity Operating Temperature & Humidity Certification Information Model No. Country of Manufacture ISO 9001 Qualified Manufacturer	LifeCam Dashboard provides access to animated video special effect features and webcam controls  Add photos to Windows Live Spaces with one mouse click  CMOS 2.0 sensor technology  • Motion Video: 800X600 pixel resolution*  • Still Image: 8.0 megapixel interpolated*  67° diagonal field of view  • Digital pan, digital tilt, vertical tilt, and swivel pan, and 5x digital zoom  • Always focused from 21" to 60" depth of field  • Automatic image adjustment with manual overwrite  Integrated microphone and noise cancellation  Unidirectional noise cancelling microphone  • Webcam Stand (2.8 X 2.6 X 11.4 inches)  • Universal Mounting Clip  Carrying Case Included  -40 °F (-40 °C) to 140 °F (60 °C) at <5% to 65% relative humidity (non-condensing)  32° F (0° C) to 104 °F (40 °C) at <5% to 80% relative humidity (non-condensing)  1355  People's Republic of China (PRC)  Yes  • FCC Declaration of Conformity (USA)  • UL and cUL Listed Accessory (USA and Canada)  • ICES-003 data on file (Canada)
Webcam Controls & Effects Blogging Feature Imaging Features Sensor Resolution Field of View Imaging Features  Product Feature Performance Audio Features  Microphone technology Mounting Features  Additional Features  Storage Temperature & Humidity Operating Temperature & Humidity Certification Information Model No. Country of Manufacture ISO 9001 Qualified Manufacturer	LifeCam Dashboard provides access to animated video special effect features and webcam controls  Add photos to Windows Live Spaces with one mouse click  CMOS 2.0 sensor technology  • Motion Video: 800X600 pixel resolution*  • Still Image: 8.0 megapixel interpolated*  67° diagonal field of view  • Digital pan, digital tilt, vertical tilt, and swivel pan, and 5x digital zoom  • Always focused from 21° to 60° depth of field  • Automatic image adjustment with manual overwrite  Integrated microphone and noise cancellation  Unidirectional noise cancelling microphone  • Webcam Stand (2.8 X 2.6 X 11.4 inches)  • Universal Mounting Clip  Carrying Case Included  -40 °F (-40 °C) to 140 °F (60 °C) at <5% to 65% relative humidity (non-condensing)  32° F (0° C) to 104 °F (40 °C) at <5% to 80% relative humidity (non-condensing)  1355  People's Republic of China (PRC)  Yes  • FCC Declaration of Conformity (USA)  • UL and cUL Listed Accessory (USA and Canada)  • ICES-003 data on file (Canada)  • CE Declaration of Conformity, Safety and EMC (European Union)
Webcam Controls & Effects Blogging Feature Imaging Features Sensor Resolution Field of View Imaging Features  Product Feature Performance Audio Features  Microphone technology Mounting Features  Additional Features  Storage Temperature & Humidity Operating Temperature & Humidity Certification Information Model No. Country of Manufacture ISO 9001 Qualified Manufacturer	LifeCam Dashboard provides access to animated video special effect features and webcam controls  Add photos to Windows Live Spaces with one mouse click  CMOS 2.0 sensor technology  • Motion Video: 800X600 pixel resolution*  • Still Image: 8.0 megapixel interpolated*  67° diagonal field of view  • Digital pan, digital tit, vertical tit, and swivel pan, and 5x digital zoom  • Always focused from 21" to 60" depth of field  • Automatic image adjustment with manual overwrite  Integrated microphone and noise cancellation  Unidirectional noise cancelling microphone  • Webcam Stand (2.8 X 2.6 X 11.4 inches)  • Universal Mounting Clip  Carrying Case included  -40 "F (-40 "C) to 140 "F (60 "C) at <5% to 65% relative humidity (non-condensing)  32° F (0" C) to 104 "F (40" C) at <5% to 80% relative humidity (non-condensing)  1355  People's Republic of China (PRC)  Yes  • FCC Declaration of Conformity (USA)  • UL and cUL Listed Accessory (USA and Canada)  • CE Se-003 data on file (Canada)  • CE Declaration of Conformity, Safety and EMC (European Union)  • GOST Certificate (Russia)  • TUV-T Certificate (European Union)
Webcam Controls & Effects Blogging Feature Imaging Features Sensor Resolution Field of View Imaging Features  Product Feature Performance Audio Features  Microphone technology Mounting Features  Additional Features  Storage Temperature & Humidity Operating Temperature & Humidity Certification Information Model No. Country of Manufacture ISO 9001 Qualified Manufacturer	4,000 actuations  LifeCam Dashboard provides access to animated video special effect features and webcam controls  Add photos to Windows Live Spaces with one mouse click  CMOS 2.0 sensor technology  • Motion Video: 800X600 pixel resolution*  • Still Image: 8.0 megapixel interpolated*  67° diagonal field of view  • Digital pan, digital tilt, vertical tilt, and swivel pan, and 5x digital zoom  • Always focused from 21" to 60" depth of field  • Automatic image adjustment with manual overwrite  Integrated microphone and noise cancellation  Unidirectional noise cancelling microphone  • Webcam Stand (2.8 X 2.6 X 11.4 inches)  • Uhiversal Mounting Clip  Carrying Case Included  40 °F (-40 °C) to 140 °F (60 °C) at <5% to 65% relative humidity (non-condensing)  32° F (0° C) to 104 °F (40 °C) at <5% to 80% relative humidity (non-condensing)  1355  People's Republic of China (PRC)  Yes  • FCC Declaration of Conformity (USA)  • UL and cUL Listed Accessory (USA and Canada)  • ICES-003 data on file (Canada)  • CE Declaration of Conformity, Safety and EMC (European Union)  • GOST Certificate (Russia)  • TUV-T Certificate (European Union)  • WCCI Certificate (European Union)
Webcam Controls & Effects Blogging Feature Imaging Features Sensor Resolution Field of View Imaging Features  Product Feature Performance Audio Features  Microphone technology Mounting Features  Additional Features  Storage Temperature & Humidity Operating Temperature & Humidity Certification Information Model No. Country of Manufacture ISO 9001 Qualified Manufacturer	4,000 actuations  LifeCam Dashboard provides access to animated video special effect features and webcam controls  Add photos to Windows Live Spaces with one mouse click  CMOS 2.0 sensor technology  • Motion Video: 800x600 pixel resolution*  • Still Image: 8.0 megapixel interpolated*  67° diagonal field of view  • Digital pan, digital tilt, vertical tilt, and swivel pan, and 5x digital zoom  • Always focused from 21" to 60" depth of field  • Automatic image adjustment with manual overwrite  Integrated microphone and noise cancellation  Unidirectional noise cancelling microphone  • Webcam Stand (2.8 X 2.6 X 11.4 inches)  • Universal Mounting Clip  Carrying Case Included  -40 "F (-40 "C) to 140 "F (60 "C) at <5% to 65% relative humidity (non-condensing)  32° F (0° C) to 104 "F (40 "C) at <5% to 80% relative humidity (non-condensing)  1355  People's Republic of China (PRC)  Yes  • FCC Declaration of Conformity (USA)  • UL and cUL Listed Accessory (USA and Canada)  • ICES-003 data on file (Canada)  • ICES-003 data on file (Canada)  • CE Declaration of Conformity, Safety and EMC (European Union)  • GOST Certificate (Russia)  • TUV-T Certificate (European Union)  • VCCI Certificate (Lipapn)  • ACA/MED Declaration of Conformity (Australia and New Zealand)
Webcam Controls & Effects Blogging Feature Imaging Features Sensor Resolution Field of View Imaging Features  Product Feature Performance Audio Features  Microphone technology Mounting Features  Additional Features  Storage Temperature & Humidity Operating Temperature & Humidity Certification Information Model No. Country of Manufacture ISO 9001 Qualified Manufacturer	4,000 actuations
Webcam Controls & Effects Blogging Feature Imaging Features Sensor Resolution Field of View Imaging Features  Product Feature Performance Audio Features  Microphone technology Mounting Features  Additional Features  Storage Temperature & Humidity Operating Temperature & Humidity Certification Information Model No. Country of Manufacture ISO 9001 Qualified Manufacturer	4,000 actuations  LifeCam Dashboard provides access to animated video special effect features and webcam controls  Add photos to Windows Live Spaces with one mouse click  CMOS 2.0 sensor technology  • Motion Video: 800x600 pixel resolution*  • Still Image: 8.0 megapixel interpolated*  67° diagonal field of view  • Digital pan, digital tilt, vertical tilt, and swivel pan, and 5x digital zoom  • Always focused from 21" to 60" depth of field  • Automatic image adjustment with manual overwrite  Integrated microphone and noise cancellation  Unidirectional noise cancelling microphone  • Webcam Stand (2.8 X 2.6 X 11.4 inches)  • Universal Mounting Clip  Carrying Case Included  -40 "F (-40 "C) to 140 "F (60 "C) at <5% to 65% relative humidity (non-condensing)  32° F (0° C) to 104 "F (40 "C) at <5% to 80% relative humidity (non-condensing)  1355  People's Republic of China (PRC)  Yes  • FCC Declaration of Conformity (USA)  • UL and cUL Listed Accessory (USA and Canada)  • ICES-003 data on file (Canada)  • ICES-003 data on file (Canada)  • CE Declaration of Conformity, Safety and EMC (European Union)  • GOST Certificate (Russia)  • TUV-T Certificate (European Union)  • VCCI Certificate (Lipapn)  • ACA/MED Declaration of Conformity (Australia and New Zealand)

 $<sup>^{\</sup>star}$  One megapixel = 1,000,000 pixels. Lower resolution available when sending video via instant messaging.

Results stated herein are based on internal Microsoft testing. Individual results and performance may vary. Any device images shown are not actual size. This document is provided for informational purposes only and is subject to change without notice. Microsoft makes no warranty, express or implied, with this document or the information contained herein. Review any public use or publications of any data herein with your local legal counsel.

©2008 Microsoft Corporation. The names of actual companies and products mentioned herein may be trademarks of their respective owners.